

# B-852 Mid-range Printer

# Datasheet

- With powerful networking capabilities, the B-852 wide web printer from Toshiba delivers outstanding performance for a wide variety of environments and applications.
- This innovative industrial printer offers superior features including extremely fast processing, large internal memory, web printer controls and SNMP networking tools.



# Speed and Functionality

The B-852 offers high-speed printing and enhanced processing via an extensive choice of interfaces – including USB 2.0 and internal LAN. The options of serial interfaces provide additional flexibility and choice, making the B-852 adaptable to the widest variety of environments and applications.

## **High Print Quality**

The 216 mm printhead facilitates rapid printing of large format compliance labels in 300 dpi.





# **SPECIFICATIONS**

#### General

Print Method Thermal transfer/Direct thermal

Printhead Flat head

**Dimensions (W x D x H)** 385 x 181 x 243 mm

429 x 427 x 265 mm with supply holder installed

Weight 15.6 kg

User interface LCD (16 digits), 3 x LED, 3 x key

Operating Temperature / Humidity

5°C to 40°C / 25-85% non condensing

relative humidity (RH)

**Power Supply** AC 100 to 240 V, 50/60 Hz

#### Print

Resolution 300 dpi (11.8 dots/mm)

Maximum Print Speed 101.6 mm/second (4 ips)

Maximum Print Width216.8 mmMaximum Print Length640 mm

Barcodes UPC/EAN/JAN, Code 39, Code 93, Code 128,

EAN 128, NW7, MSI, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Postnet, RM4SCC, KIX-Code,

Customer Barcode, GS1 Databar

2D Codes Data Matrix, PDF417, QR Code, Maxi Code,

Micro PDF417, CD Code

Fonts Bitmap font, Outline font, Writable characters, TTF

#### Media

Alignment Centred

Backing Paper Width 100-242 mm

Label Thickness 0.13-0.18 mm

Inner Media Core Diameter 38-76 mm

Outer media Roll Diameter 230 mm

Media Type Roll, Fanfold

## Software & Connectivity

Printer Driver Windows 10/8/7/Vista (32/64 bit),

Windows Server 2012/Server 2008 (32/64 bit)

Interface USB 2.0 (Full Speed), LAN 10/100 Base, Parallel port,

Serial port1)

Language Mode TPCL, BCI (function)

Label Software BarTender UltraLite

# **Options**

For B-852 Cutter module, expansion I/O board,

RTC (real time clock)

1) Optional



### Ribbon

Ribbon Width 120-220 mm
Ribbon Core Size 25.4 mm (1 inch)

Fixed Core Length 240 mm

Max. Ribbon Length 300 m

Max. Ribbon Diameter 40 mm

For more information, please contact your local Toshiba partner.



Südstrasse 4a | 3110 Münsingen T: +41 31 838 50 50 | F: +41 31 838 50 55 info@labeltech.ch | labeltech.ch